

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:	J. Of.
Dae-Young Kim et al.	Examiner: K. Tran
Application No.: 09/499,014	Group Art Unit: 2631
Filed: February 4, 2000	Docket No: CX020003
Title: METHOD AND APPARATUS FOR	
THE CONTROL OF MODEM TRANSMIT POWER	RECEIVE
Commissioner for Patents	0CT 1 1 200

Technology Center 2600

REPLY TO OFFICE ACTION AND AMENDMENT UNDER 37 C.F.R. § 1.111

Dear Commissioner:

Washington, DC 20231

In reply to the Office Action mailed May 15, 2001, Applicants respectfully request reconsideration of the current Application.

FEES/EXTENSION OF TIME

Please charge Deposit Account No. 13-4773 for any and all fees required under 37 C.F.R. §§ 1.16 or 1.17, or credit Deposit Account No. 13-4773 for any and all refunds. One copy of this page is enclosed for deposit account purposes.

Applicants hereby petition for an extension of time of one (1) month under 37 C.F.R.

§ 1.136, having a fee of \$110. 10/10/2001 SZEWDIE1 00000024 134773 09499014

01 FC:115

110.00 CH

I hereby certify that this correspondence is being deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to: Assistant Commissioner for Patents, Washington, DC 20231 on:

9/13/01

Elaune

E/a;ne

Printed on Timed

REPLACEMENT PARAGRAPHS

Replace the 4th paragraph on page 11, beginning at line 11, with:

What has been described is one of the ways by which the analog modem transmit power level can be adjusted. It should be noted that the transmit power level is also determined by the transmit constellation. However, the transmit constellation itself is hard to change to obtain different upstream transmit powers, since its modification will change the error probability of the upstream receiver. Therefore, in general, only mapping parameters are modified to change upstream transmit

Replace the 2nd paragraph on page 12, beginning at line 6, with:

In the above section a technique for PCM downstream spectral shaping or precoding of data signals is described. In this section there is described a precoding technique for PCM upstream precoding of data signals.

RECEIVED

OCT 1 1 2001
Technology Center 2600